



## Self-Leveling Underlayments Designed to Outperform the Competition

**Custom****TECH**<sup>®</sup>  
DESIGNED FOR ALL FLOORING

- Low Prep Formulas: Sweep, Prime and Pour
- Cures fast and develops high early-strength for quick installation
- Exceeds ASTM requirements for resilient floor covering installations



**CUSTOM**<sup>®</sup>  
FLOORING INSTALLATION SYSTEMS



## TechLevel™ XP-1

### High Performance Calcium Aluminate Based Self-Leveling Underlayment

- Greater than 5,500 PSI compressive strength
- Abrasion Resistant – Holds up to traffic during construction
- High flow formula has excellent handling and exceptional flow retention properties
- Low prep formula: Sweep, prime & pour

## TechLevel™ 150

### Premium Calcium Aluminate Based Self-Leveling Underlayment

- High flow formula has excellent handling and exceptional flow retention properties
- Low prep formula: Sweep, prime & pour
- Crack resistant
- Greater than 4,300 PSI compressive strength resilient floor covering installations

## TechLevel™ 100

### Calcium Aluminate Based Self-Leveling Underlayment

- Crack Resistant
- Levels Floors from 1/4" to 1-1/2" (6 mm to 3.8 cm) Thick
- Exceeds ASTM requirements for resilient floor covering installations

#### Uses:

Suitable as an Underlayment for:

- Carpet
- Wood, parquet
- Vinyl composition tile (VCT)
- Sheet vinyl flooring
- Laminated flooring
- Vitreous, semi-vitreous or non-vitreous tile
- Ceramic, mosaic, quarry, cement body tile
- Impervious porcelain and glass tile
- Brick and stone veneer
- Cement-based precast terrazzo
- Natural stone tile
- Stone, terrazzo

ITEM CODE	SIZE	PACKAGE
TLXP150T	50 lb. (22.68 kg)	Bag
TL15050T	50 lb. (22.68 kg)	Bag
TL10050T	50 lb. (22.68 kg)	Bag

#### Coverage

Typical square foot coverage per 50 lb. bag  
(square meter per 22.68 Kg)

THICKNESS	COVERAGE
1/8" (3.18 mm)	50 ft² (4.6 m²)
1/4" (6.35 mm)	25 ft² (2.3 m²)
1/2" (12.7 mm)	12.5 ft² (1.15 m²)
1" (25.4 mm)	6.25 ft² (0.56 m²)
1.5" (38.1 mm)	4.17 ft² (0.38 m²)
2" (50.8 mm)	3.13 ft² (0.29 m²)

Chart for estimating purposes. Coverage may vary based on installation practices and jobsite conditions. For more tile and joint sizes, use the material calculator at CustomBuildingProducts.com or contact CUSTOM Technical Services at 800-282-8786.

**Warranty:** Flooring Installation Systems products are backed by up-to a 15-year warranty. See CustomTechFlooring.com for full warranty information including limitations and exclusions.

©2016 Custom Building Products. All rights reserved. The CUSTOM® and CustomTech® logos, and select product logos are registered trademarks of Custom Building Products, Inc. CUSTOM may make product modifications at any time without notice. Visit customtechflooring.com for updated technical data sheets and SDS information.

Custom Building Products  
800-272-8786  
CustomTechFlooring.com  
SS175 6/16N