



Self-Leveling Underlayments Designed to Outperform the Competition

CustomTECH[®]
FLOORING PREPARATION SYSTEMS

- Low Prep Formulas: Sweep, Prime and Pour
- Cures fast and develops high early-strength for quick installation
- Exceeds ASTM requirements for resilient floor covering installations



CUSTOM[®]

A QUIKRETE[®] COMPANY



TechLevel™ 100

Calcium Aluminate Based Self-Leveling Underlayment

- Crack Resistant
- Levels Floors from 1/4" to 1-1/2" (6 mm to 3.8 cm) Thick
- Exceeds ASTM requirements for resilient floor covering installations



TechLevel™ WSF

Fiber Reinforced Self-Leveling Underlayment for Wood Subfloors

- No lath required for plywood and OSB subfloors
- Low Prep Formula
- Compatible with most radiant heating systems
- High flow formula has excellent handling and exceptional flow retention properties
- Can be used in place of backerboard over most applications



TechLevel™ 125

Calcium Aluminate Based Deep Pour Self-Leveling Underlayment

- High strength up to 3" in one pour for thick build applications
- Low Prep Formula
- Crack resistant formula
- Ideal for inconsistent substrates



TechLevel™ XP-1

High Performance Calcium Aluminate Based Self-Leveling Underlayment

- Greater than 5,500 PSI compressive strength
- Abrasion Resistant – Holds up to traffic during construction
- High flow formula has excellent handling and exceptional flow retention properties
- Low prep formula



TechLevel™ 150

Premium Calcium Aluminate Based Self-Leveling Underlayment

- High flow formula has excellent handling and exceptional flow retention properties
- Low prep formula
- Crack resistant
- Greater than 4,300 PSI compressive strength resilient floor covering installations



TechLevel™ HPT

High Performance Calcium Aluminate Based Self-Leveling Topping

- Versatile product, performs as high performance SLU or interior wear surface topping
- Compressive strength > 6,000 psi
- Cures fast; walkable in as little as 2 hours and accepts coatings in 24 hours
- Crack resistant, exceptionally smooth surface

Uses:

Suitable as an Underlayment for:

- Carpet
- Wood, parquet
- Vinyl composition tile (VCT)
- Sheet vinyl flooring
- Laminated flooring
- Vitreous, semi-vitreous or non-vitreous tile
- Ceramic, mosaic, quarry, cement body tile
- Impervious porcelain and glass tile
- Brick and stone veneer
- Cement-based precast terrazzo
- Natural stone tile
- Stone, terrazzo

| ITEM CODE | SIZE | PACKAGE |
|-----------|-------------------|---------|
| TL10050T | 50 lb. (22.68 kg) | Bag |
| TL12550T | 50 lb. (22.68 kg) | Bag |
| TL15050T | 50 lb. (22.68 kg) | Bag |
| TLWSF50T | 50 lb. (22.68 kg) | Bag |
| TLXP150T | 50 lb. (22.68 kg) | Bag |
| TLHPT50T | 50 lb. (22.68 kg) | Bag |

Coverage

Typical square foot coverage per 50 lb. bag (square meter per 22.68 Kg)

| ITEM CODE | COVERAGE | THICKNESS |
|-----------|---|----------------|
| TL10050T | 22.99 - 24.10 ft ² (2.14 - 2.24 m ²) | 1/4" (6.35 mm) |
| TL12550T | 21.58 - 22.74 ft ² (2.00 - 2.11 m ²) | 1/4" (6.35 mm) |
| TL15050T | 22.99 - 24.10 ft ² (2.14 - 2.24 m ²) | 1/4" (6.35 mm) |
| TLWSF50T | 22.38 - 23.57 ft ² (2.08 - 2.19 m ²) | 1/4" (6.35 mm) |
| TLXP150T | 22.75 - 23.66 ft ² (2.11 - 2.20 m ²) | 1/4" (6.35 mm) |
| TLHPT50T | 21.57 - 22.85 ft ² (2.00 - 2.12 m ²) | 1/4" (6.35 mm) |

Chart for estimating purposes. Coverage may vary based on installation practices and jobsite conditions. For more tile and joint sizes, use the material calculator at CustomBuildingProducts.com or contact CUSTOM Technical Services at 800-282-8786.

Warranty: Flooring Installation Systems products are backed by up-to a 25-year warranty. See CustomTechFlooring.com for full warranty information including limitations and exclusions.

©2018 Custom Building Products. All rights reserved. The CUSTOM® and CustomTech® logos, and select product logos are registered trademarks of Custom Building Products, Inc. CUSTOM may make product modifications at any time without notice. Visit customtechflooring.com for updated technical data sheets and SDS information.

Custom Building Products
800-272-8786
CustomTechFlooring.com
SS175 8/18R



CUSTOM®

A QUIKRETE® COMPANY